

BOLON BY YOU

TECHNICAL INFORMATION

Construction: Woven vinyl flooring, product standard EN 15114/EN 1307. Bolon.com for updated information

Included in EN 15114/EN 1307		Use classification		ISO 10874	33 Heavy commercial	
		Weight	Rolls Tiles	ISO 8543	2,9 kg/m ² 3,9 kg/m ²	
		Thickness	Rolls Tiles	ISO 1765	2,5 mm 3,0 mm	
		Roll dimension	Width Length	EN 426	2000 mm 25 m	
		Tile dimension	Tiles	EN 994	500 x 500 mm. 20 pcs/box, 5 sqm	
		Castor Chair		EN 985	Continuous use	
		Body Voltage		EN 1815***	Fulfilled	
		Thermal resistance		ISO 8302	Suitable for underfloor heating	
		Impact sound insulation**	Rolls Tiles	EN ISO 10140	11 dB 11 dB	
		Airborne sound absorption**		EN ISO 354	0,05	
		Colour fastness to light**		EN ISO 105-B02	8	
		Dimension stability	Rolls Tiles	ISO 2551 EN 986	Fulfilled Fulfilled	
	Additional tests		Anti slip property		DIN 51130	R9
			Friction		EN 13893	> 0,3
		Pendulum		EN 13036-4	94-95	
		Reaction to fire		EN 13501-1	B _s -s1	
		Critical radiant flux		ASTM E 648	Class 1	
		Smoke density	Rolls Tiles	ASTM E 662	< 450 < 450	
		Emission TVOC		EN ISO 16000-10	<50 µg/m ² h	
Certifications		CE certificate		EN 14041	No 0402-CPR-419007	
		Floor Score certificate	Rolls Tiles	SCSEC-10.2-2007	SCS-FS-02007 SCS-FS-02240	
		Classification	Rolls Tiles	CSTB	Under testing at time of printing Under testing at time of printing	

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.



Bolon Flooring
is recyclable



CERTIFIED BY
SCS Global Services



MADE USING
BEST ENVIRONMENTAL
PRACTICE™

BYGGVARUBEDÖMNINGEN