
















# BOLON FLOORING

# SILENCE

## PRODUCT SPECIFICATION

Woven vinyl flooring, product standard EN 1307.

GENERAL INFORMATION			ROLLS	TILES	ACOUSTIC FELT
	<b>Use classification</b>	EN 1307	33 Heavy	33 Heavy	33 Heavy
	<b>Weight</b>	ISO 8543	3,0 kg/m <sup>2</sup>	4,0 kg/m <sup>2</sup>	3,7 kg/m <sup>2</sup>
	<b>Thickness</b>	ISO 1765	2,5 mm	3,0 mm	5,1 mm
	<b>Roll dimension</b>	ISO 24341	2000 mm, 25 m		
	<b>Tile dimension</b>	EN ISO 24342		500 mm	500 mm
	<b>Recycled content</b>	ISO 14021	66%	72%	69%
<b>DURABILITY</b>					
	<b>Castor Chair</b>	EN 985	Continuous use	Continuous use	Continuous use
	<b>Colour fastness to light</b>	EN ISO 105-B02	>7	>7	>7
	<b>Dimension stability</b>	ISO 2551 EN 986	Fulfilled	Fulfilled	Fulfilled
<b>ACOUSTIC</b>					
	<b>Impact sound insulation</b>	EN ISO 10140	12 dB	13 dB	21 dB
	<b>Airborne sound absorption</b>	EN ISO 354 $\alpha_w$	0,05	0,05	0,05
	<b>Airborne sound absorption</b>	EN ISO 354 $\alpha_s$	250 Hz 0,01 500 Hz 0,01 1000 Hz 0,05 2000 Hz 0,09	250 Hz 0,01 500 Hz 0,01 1000 Hz 0,05 2000 Hz 0,09	250 Hz 0,01 500 Hz 0,19 1000 Hz 0,12 2000 Hz 0,09
<b>ADDITIONAL PROPERTIES</b>					
	<b>Anti slip property</b>	DIN 51130	R9	R9	R9
	<b>Pendulum</b>	EN 13036-4	94-95	94-95	94-95
	<b>Dynamic coefficient of Friction</b>	EN 13893	>0,3	>0,3	>0,3
	<b>Body Voltage</b>	EN 1815*	Fulfilled	Fulfilled	Fulfilled
	<b>Thermal resistance</b>	ISO 8302/ EN 12667	Suitable for underfloor heating	Suitable for underfloor heating	Suitable for underfloor heating
<b>FIRE PROPERTIES</b>					
	<b>Reaction to fire</b>	EN 13501-1	B <sub>n</sub> -s1	B <sub>n</sub> -s1	B <sub>n</sub> -s1
	<b>Critical radiant flux</b>	ASTM E 648	Class 1	Class 1	Class 1
	<b>Smoke density</b>	ASTM E 662	<450	<450	<450

\* Typical value

# BOLON FLOORING SILENCE

## CERTIFICATES

For complete information and market specific certificate, visit [bolon.com](http://bolon.com) or contact [sales.support@bolon.com](mailto:sales.support@bolon.com)

		ROLLS	TILES	ACOUSTIC FELT
<b>CE</b>	EN 14041:2004 och EN 14041:2004/AC:2006	0402-CPR-419005	0402-CPR-419005	0402-CPR-419013
<b>UK CA</b>	EN 14041:2004/AC:2006	0086 CPR 770145	0086 CPR 770145	0086 CPR 770147
<b>LIFE CYCLE PERSPECTIVE</b>				
EPD	ISO 14025 och EN 15804	S-P-03839	S-P-03985	S-P-03986
Embodied Carbon	EPD modul A1-A3	5,18 kg CO <sub>2</sub> eq.	6,19 kg CO <sub>2</sub> eq.	5,47 kg CO <sub>2</sub> eq.
DGNB Navigator		Yes	Yes	Yes
GreenTag - GreenRate		Yes	Yes	No
<b>INDOOR AIR</b>				
M1		No	No	Yes
FloorScore		Yes	Yes	Yes
French VOC		Yes	Yes	Yes
Rekommenderas av NAAF		Yes	Yes	Yes
<b>PRODUCT AND RAW MATERIAL</b>				
BASTA		Yes	Yes	Yes
Byggsvarubedömningen		Yes	Yes	Yes
ECOproduct		Yes	Yes	Yes
eBVD		Yes	Yes	Yes
GBR kretsloppsmärkning		Yes	Yes	Yes
Best Practice PVC		Yes	Yes	Yes
GreenTag - PHD		Yes	Yes	Yes
Declare		Yes	Yes	Yes



# BOLON

Bolon HQ: Industrivägen 12, 523 90 Ulricehamn, Sweden  
[bolon.com](http://bolon.com) | [info@bolon.com](mailto:info@bolon.com) | [@bolonofficial](https://www.instagram.com/bolonofficial)

March 2025