

BOLON FLOORING

BOLON BY PATRICIA URQUIOLA

PRODUCT SPECIFICATION

Woven vinyl flooring, product standard EN 1307.

GENERAL INFORMATION

			ROLLS
	Use classification	EN 1307	33 Heavy
	Weight	ISO 8543	0.65 lb/ sqft (3.1 kg/ m²)
	Thickness	ISO 1765	0.09" (2.3 mm)
	Roll dimension	ISO 24341	6'7" x 82" (2 x 25 m)
	Tile dimension	EN ISO 24342	
	Recycled content	ISO 14021	66%

DURABILITY

	Castor chair	EN 985	Continuous use
	Color fastness to light	EN ISO 105-B02	>7
	Dimension stability	ISO 2551 EN 986	Fulfilled

ACOUSTIC

	Impact sound insulation	EN ISO 10140	9 dB
	Airborne sound absorption	EN ISO 354 α_w	0.05
	Airborne sound absorption	EN ISO 354 α_s	250 Hz 0.01 500 Hz 0.01 1000 Hz 0.05 2000 Hz 0.09

ADDITIONAL PROPERTIES

	Anti slip property	DIN 51130	R9
	Pendulum	EN 13036-4	88-93
	Dynamic coefficient of friction	EN 13893	>0.3
	Body voltage	EN 1815*	Fulfilled
	Thermal resistance	ISO 8302/ EN 12667	Suitable for underfloor heating

FIRE PROPERTIES

	Reaction to fire	EN 13501-1	B _n -s1
	Critical radiant flux	ASTM E 648	Class 1
	Smoke density	ASTM E 662 Flaming	<450

* Typical value

BOLON FLOORING

BOLON BY PATRICIA URQUIOLA

CERTIFICATES

For complete information and market specific certificate, visit bolon.com or contact bolon@mattersurfaces.com

ROLLS		
	EN 14041:2004 och EN 14041:2004/AC:2006	0402-CPR-419005
	EN 14041:2004/AC:2006	0086 CPR 770145
LIFE CYCLE PERSPECTIVE		
EPD	ISO 14025 och EN 15804	S-P-03839
Embodied Carbon	EPD modul A1-A3	5.18 kg CO ₂ eq.
DGNB Navigator		Yes
GreenTag - GreenRate		Yes
INDOOR AIR		
M1		No
FloorScore		Yes
French VOC		Yes
Rekommenderas av NAAF		Yes
PRODUCT AND RAW MATERIAL		
BASTA		Yes
Byggsvarubedömningen		Yes
ECOproduct		Yes
eBVD		Yes
GBR kretsloppsmärkning		Yes
Best Practice PVC		Yes
GreenTag - PHD		Yes
Declare		Yes



BOLON

Matter Surfaces- Exclusive North American Partner: 27 W 24th St Suite 601, New York, NY 10010
bolon.com | info@bolon.com | [@bolonofficial](https://twitter.com/bolonofficial)

March 2025