

FLOW

TECHNICAL INFORMATION


Construction: Woven vinyl flooring, product standard EN 1307. Bolon.com for updated information

Included in EN 1307		Use classification		ISO 10874	32 General commercial	
		Weight	Rolls Tiles	ISO 8543	2,8 kg/m ² 3,8 kg/m ²	
		Thickness	Rolls Tiles	ISO 1765	2,3 mm 2,9 mm	
		Roll dimension	Width Length	EN 426	2000 mm 25 m	
		Tile dimension		EN 994	500 x 500 mm. 20 pcs/box, 5 sqm	
		Castor Chair		EN 985	Continous use	
		Body Voltage		EN 1815**	Fulfilled	
		Thermal resistance		ISO 8302	Suitable for underfloor heating	
		Impact sound insulation*		EN ISO 10140	13 dB	
		Airborne sound absorption*		EN ISO 354	0,05	
		Colour fastness to light*		EN ISO 105-B02	8	
		Dimension stability	Rolls Tiles	ISO 2551 EN 986	Fulfilled Fulfilled	
	Additional tests		Anti slip property		DIN 51130	R10
			Friction		EN 13893	> 0,3
		Pendulum		EN 13036-4	97-101	
		Reaction to fire		EN 13501-1	B _{fl} -s1	
		Critical radiant flux		ASTM E 648	Class 1	
		Smoke density		ASTM E 662	< 450	

CSTB

U3P2 E1/2 C1 12_14-1691_V1

Certifications



* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.