
















# Technical information Flow

Construction: Woven vinyl flooring, product standard EN 1307

Included in EN 1307

	<b>Use classification</b>		ISO 10874	33 Heavy commercial
	<b>Weight</b>	Rolls Tiles	ISO 8543	3,0 kg/m <sup>2</sup> 4,0 kg/m <sup>2</sup>
	<b>Thickness</b>	Rolls Tiles	ISO 1765	2,6 mm 3,2 mm
	<b>Roll dimension</b>	Width Length	EN 426	2000 mm 25 m
	<b>Tile dimension</b>		EN 994	500 x 500 mm. 20 St/Box, 5 m <sup>2</sup>
	<b>Castor Chair</b>		EN 985	Continous use
	<b>Body Voltage</b>		EN 1815**	Fulfilled
	<b>Thermal resistance</b>		ISO 8302	Suitable for underfloor heating
	<b>Impact sound insulation*</b>		EN ISO 10140	14 dB
	<b>Airborne sound absorption*</b>		EN ISO 354	0,10
	<b>Colour fastness to light*</b>		EN ISO 105-B02	7
	<b>Dimension stability</b>	Rolls Tiles	ISO 2551 EN 986	Fulfilled Fulfilled

Additional tests

	<b>Anti slip property</b>		DIN 51130	R9
	<b>Friction</b>		EN 13893	> 0,3
	<b>Pendulum</b>		EN 13036-4	104-107
	<b>Reaction to fire</b>		EN 13501-1	B <sub>fl</sub> -s1
	<b>Critical radiant flux</b>		ASTM E 648	Class 1
	<b>Smoke density</b>		ASTM E 662	<450
	<b>Emission</b>		EN ISO 16000-10	<20µg/m <sup>2</sup> h

Certifications

<b>CE certificate</b>		EN 14041	No 0402-CPR-419009
<b>Floor Score certificate</b>	Rolls Tiles	SCSEC-10.2-2007	SCS-FS-02007 SCS-FS-02240
<b>Classification</b>	Rolls Tiles	CSTB	Not tested at time of printing Not tested at time of printing

\* Typical value

\*\* EN 1815 replaces ISO 6356

Some of the collections are design protected.

